

MATERIAL SAFETY DATA SHEET



Pro ColorFlex Ink Corporation

Pro ColorFlex Ink Corporation

3588 Arden Road

Hayward, CA 94545

Tel: 510-293-3033 Fax: 510-293-3038

Emergency Telephone No.

800-485-2605

Date Prepared: 04/03/98

Revised: 07/07/2008

PRODUCT HMIS RATINGS

Health.....2 (Slight)

Flammability.....3 (High)

Reactivity.....0 (Minimal)

SECTION A - PRODUCT INFORMATION

Trade Name: Supermarking Ink

Product ID No: Varies With Color

Product Class: Stamp Ink

Manufacturer: Pro ColorFlex Ink Corp.

3588 Arden Road

Hayward, CA 94545

SECTION B - HAZARDOUS COMPONENTS

Ethanol	CAS # 64-17-5	Flammable Liquid, Eye and Skin Irritant.	1000 ppm (ACGIH TLV-TWA) 1000 ppm (OSHA PEL)
Isopropanol	CAS # 67-63-0	Flammable Liquid, Eye and Skin Irritant	400 ppm (ACGIH TLV-TWA) 400 ppm (ACGIH TLV-TWA)
Methanol	CAS # 67-56-1	Flammable Liquid, Eye, Skin and Respiratory Irritant.	200 ppm (ACGI TLV-TWA) 400 ppm (OSHA PEL)
Ethyl Acetate	CAS # 141-78-6	Flammable Liquid, Eye, Skin and Respiratory Irritant.	400 ppm (ACGI TLV-TWA) 400 ppm (OSHA) PEL

SECTION C - PHYSICAL DATA

APPEARANCE: Thin Colored Liquid

PHYSICAL STATE: Liquid

EVAPORATION RATE (VS BUTYL ACETATE): Faster

% VOLATILE BY WEIGHT: 63.00

BOILING RANGE (°F): 171

ODOR: Alcoholic

VAPOR DENSITY: Heavier

SOLUBILITY IN WATER: Insoluble

SECTION D - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 73 OF Tagliabue Closed Tester (ASTM D 56-79)

FLAMMABLE LIMITS: Lower: 3.3% Upper: 19.00%

EXTINGUISHING MEDIA: Alcohol Foam, CO₂ Dry Chemical, Water Fog.

SPECIAL FIREFIGHTING PROCEDURES: Class I-B Flammable Liquid. Vapors from this product may concentrate in confined spaces and form an explosive mixture.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product may produce hazardous fumes or hazardous decomposition products> Heated containers may rupture violently from excessive heat.

SECTION E - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Mixture. See section B, Hazardous components of mixture.

PRIMARY ROUTES OF ENTRY: Skin contact. Inhalation.

EFFECTS OF ACUTE OVEREXPOSURE: Prolonged or repeated exposure to this product may dry skin and cause dermatitis. Prolonged or repeated exposure may cause kidney, liver, lungs and heart damage.

SECTION F - EMERGENCY FIRST AID PROCEDURES:

EYES: Flush immediately with plenty of water for at least 15 minutes. Remove contact lenses if worn. Get medical attention if irritation persists.

SKIN: Thoroughly wash exposed area with soap and water. Remove contaminated clothing.

INGESTION: If swallowed, get medical attention immediately. Induce vomiting immediately, as directed by medical personnel.

INHALATION: Remove individual to fresh air.

SECTION G - REACTIVITY DATA

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable.

INCOMPATIBILITY: Oxidizers and alkali metal hydroxides.

CONDITIONS TO AVOID: Hot storage (above 80 °F), sparks and open flames. Avoid contact with strong oxidizing agents.

SECTION H - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

SMALL SPILL: Remove all ignition sources. Small spills may be collected with absorbent materials. Wash area with soap and water, collect rinsates and containerize for disposal.

LARGE SPILL: Remove all ignition sources. Vapors are heavier than air and will concentrate at ground level. Contain spill immediately. Prevent from getting into public sewer, water systems or surface waters. Place in suitable container for disposal.

WASTE DISPOSAL INFORMATION: Dispose in accordance with Local, State and Federal regulations.

SECTION I - PROTECTIVE EQUIPMENT TO BE USED

VENTILATION: Provide sufficient mechanical ventilation.

PROTECTIVE GLOVES: If prolonged or repeated contact, wear impervious gloves.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised.

RESPIRATORY PROTECTION: Not necessary under normal use conditions.

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash stations should be readily available. Apron.

SECTION J - STORAGE AND HANDLING

Keep in cool, dry ventilated storage and in closed containers away from all sources of ignition. Wash thoroughly after handling. Ignition may occur at temperatures below those published in the literature as autoignition or ignition temperatures.

SECTION K - SPECIAL PRECAUTIONS

WARNING: Hot organic chemical vapors or mists are susceptible to sudden spontaneous combustion when mixed with air. Ignition may occur at temperatures below those published in the literature as autoignition or ignition temperatures.